

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-222444

(43)Date of publication of application : 12.08.1992

(51)Int.Cl.

H02K 16/00

G02B 7/04

G03B 3/10

G03B 13/34

(21)Application number : 02-412616

(71)Applicant : KYOCERA CORP

(22)Date of filing : 21.12.1990



(72)Inventor : YAMAMOTO MASARU

## (54) ROTARY DRIVER FOR TUBULAR BODY

## (57)Abstract:

PURPOSE: To obtain a rotary driver effective for rotary driving of a tubular body by constituting the rotary driver of a stator in which a pair of poles mounted on ring type first and second yokes provided with coils are disposed oppositely and a permanent magnet rotor interposed between the poles.

CONSTITUTION: Upon application of a pulse voltage on a first coil 21, flux is induced in a second yoke 11 to excite a pair of poles 13 and a rotor 31 rotates according to first and second outer peripheral poles 13a, 13b and an inner peripheral pole 13c. Upon subsequent application of a pulse voltage on a second coil 22, flux is induced in a second yoke 12 and a pair of poles 17 are excited. Consequently, the rotor 31 rotates according to first and second outer peripheral poles 17a, 17b and an inner peripheral pole 17c. When power is fed alternately to the first and second coils 21, 22, the rotor 31 sustains rotation. When other rotors 32, 33, 34 rotate similarly, the rotors are interlocked with a pinion 35 and a rotary cylinder 40 is rotary driven.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's  
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office